

AIRTECH 1 & 2 ATEX AIR OPERATED INDUSTRIAL VACUUM CLEANER

The Airtech 1 and 2 ATEX machines are supercharged air operated industrial vacuum cleaners for use on dry materials. The high capacity Airtech is fully operated via an air supply attached to the top of the vacuum meaning no electricity is required unlike normal vacuum cleaners

FEATURES

- Works from plant air supply
- Low maintenance
- Low life-time costs (no motors or fans to replace)
- Develops vacuum up to 3 times greater than normal industrial vacuums
- Also available in twin venturi for extra power
- Choice of 38/51mm accessory kits

HEPA FILTRATION AVAILABLE IF REQUIRED.
PRICES ON APPLICATION.



ATEX 
CERTIFIED

ATEX  II2 GD c IIC T6*

* Equivalent to National Fire Protection Association 70: NEC Rating:

Class I Division 1** Groups A, B, C, D T6

Class II Division 1 Groups E, F, G T6

Class III

** Zone 1 only

TECHNICAL SPECIFICATIONS

Vacuum:	Up to 17" Hg
Flow Rate:	Up to 45 gallons in 24 seconds
Lift:	Up to 6m
Dimensions:	1110mm(h) x 740mm(w) x 600mm(d)
Weight:	Unloaded 54kg / 57kg
Capacity:	205 litres
Compressed Air Inlet:	¾ BSP Female valve/¾" for tree tail
Castors:	100mm

Consumption

Airtech/1

@100psi-100cfm

@80psi-80cfm

@60psi-60cfm

@40psi-40cfm

AirtechH/2

@100psi-200cfm

@80psi-160cfm

@60psi-120cfm

@40psi-80cfm